



FEEL



1. SPECIFICATIONS AND FIELDS OF EMPLOYMENT

Top class wall decoration for interior finishes, very opaque, characterized by an extraordinary tactile softness and a pleasant texture, remaining you of the soft leather and glamor of antique brushed suede leather. FEEL is used indoors in simple and shabby-chic style, where the special effect "matt & touch" accompanying the walls of an original chromatic harmony of fine "chiaroscuro", creating great emotion just by touching the finish. Thanks to the flexibility of FEEL it can be used in the the decoration of public and private environments. FEEL allows you to obtain very simple application method various different styles of extraordinary beauty. FEEL is highly washable after about three weeks from the application and it is non-flammable

2. COMPOSITION

Inorganic and organic pigments, acrylic copolymers in emulsion, soft touch polymeric microspheres, special non-toxic additives. Free from harmful substances such as lead-based or chrome solvents and pigments.

3. METHOD OF APPLICATION

Surface preparation

Sandpaper, dust and fill any imperfections with STUCCOMURO then apply a coat of FISSATIVO UNIVERSAL appropriately diluted with water: ratio from 1: 5 up to 1:10 depending on the absorption of the support. Allow drying for at least 4 hours and applying two coats of PRIMER S white, leaving at least 4-5 hours between each application.

Application:

The application of Feel is simple and fast. There are 4 different methods of application.

-Pennellato Effect

Apply a first coat of FEEL with a special SPALTER DECORA' following criss-cross directions until the entire surface has been covered.

After 30 minutes repeat the same procedure applying a second coat of FEEL on the wall following the same procedure.

The first coat may be applied with a Roller giving better coverage to the entire surface.

-Rigato Effect

Apply a first coat of FEEL with special SPALTER DECORA covering an area of about 0.70 - 1 m. immediately afterwards, comb the surface with a clean

brush ArtheMETAL RIGATO TOOL in such a way as to obtain the striped design. Repeat over the entire surface. After about 30 minutes, repeat the same procedure applying a second coat of FEEL on the wall, with the. Avoid matching the position of the first coat joints with those of the second coat.

-Spatolato Effect

Apply a first coat of FEEL with special SPALTER DECORA covering an area of about 0.70 - 1 m.; Immediately afterwards, go over the surface using The stainless steel trowel effect in diagonal and irregular movements. Repeat until the entire surface has been covered. After about 30 minutes, repeat the same procedure applying a second coat of FEEL on the wall, with the same procedure. If you want FEEL can be applied directly with a stainless steel trowel without using the SPLATER.

-Broccato Effect

Apply a first coat of FEEL with special SPALTER DECORA covering an area of about 0.70 - 1 m linear. Immediately afterwards go over the surface with a SPATOLA BROCCATO" in circular and irregular movements. Repeat until the entire surface has been covered. After about 30 minutes, repeat the same procedure applying a second coat of FEEL on the wall, with the same procedure. The first coat may be applied with a Roller giving better coverage to the entire surface.

4. TECHNICAL DATA

SPECIFIC WEIGHT: 1,103 ± 5% kg/Lt

VISCOSITY 'Brookfield 3000 Cps (R5 - RPM50) at 25°C ± 15%

DRYING TO TOUCH: to touch 4-5 hours at 20°C.

DRYING COMPLETELY: 24-48 hours at 20°C.

APPLICATION TEMPERATURE: between 5°C and 30°C

FILM ASPECT: patinated matt

COVERAGE: 5-7 m²/Lt. about (two coats)

DILUTION: Ready to use.

COLORS: From the colour chart are obtainable from our *Global Tinting System*.

PACKAGE: polyethylene cans of Lt. 2,5 e da Lt.0, 75

PRESERVATION: 24 months in the intact packages, away from temperature changes

HS-CODE: 32149000

5. ITEM OF SPECIFICATIONS



Emotion with paint ...

SPIVER s.r.l.

contrada Babbaurra S.S. 122

93100 Caltanissetta (CL)

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

www.spiver.it - info@spiver.it



FEEL



EXTERNAL USE

Decoration and protection of interior wall surfaces with high decorative painting matte soft-touch, the FEEL Spiver srl, pigmented inorganic organic, acrylic copolymers in emulsion, polymeric microspheres soft touch, S. Price includes materials and implementation, excluding the scaffolding sqm. €

N.B. The above data may be subject to change. Spiver srl assumes no responsibility for the negative results that depend on applications running outside of its control or due to causes unconnected to the quality of the product.



Emotion with paint ...

SPIVER s.r.l.

contrada Babbaurra S.S. 122
93100 Caltanissetta (CL)

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

www.spiver.it - info@spiver.it

Scheda Tecnica: FEEL SP114. Rev.1La presente scheda annulla e sostituisce le precedenti